

Comark EVt2

Multi-Use Transport Logger

Keeping temperature sensitive products, materials and ingredients within required temperature limits is vital. Customers demand it, consumers rely on it and regulations insist on it - but how to prove it?

Comark EVt temperature logger is robust, low cost and easy to use and provides a highly efficient method of logging over any distance to check that goods are kept at optimum temperatures.

Using Comark EV software, EVt loggers can be programmed to record the temperature at various stages of a journey, and the results later downloaded to a PC for immediate analysis and storage of permanent records.

- **Certified to meet Transport Standard EN 12830:1999**
EVt2 is the perfect choice for cold chain applications
- **Water and dustproof** sealed to IP67 standards for long life expectancy and accuracy
- **Large memory capacity** with 3000 memory capacity
- **LED screen** allows instant local checks on current readings and alarms
- **Alarm** indication lights instantly warn of potentially unsafe conditions allowing instant corrective actions
- **Flexible logging** frequency from 1 second to 99 hours
- **Ideal for HACCP** and other quality systems
- **Professional Version** of software aids 21CFR Part 11 Compliance
- **EVCRU Interface** required to download data to a PC

Comark uses BioCote®, the only antimicrobial solution to be awarded HACCP International Certification, to provide an important extra level of defence against cross-contamination.



Comark is the leading manufacturer and supplier of a wide range of electronic measurement instruments for temperature, humidity and pressure.



| Temperature Measurement | |
|--|--|
| Sensor | Thermistor |
| Measurement Range EVt2 | -30°C to +70°C, -22°F to +158°F |
| Scales | °C and °F |
| Displayed Resolution | 0.1° |
| System Accuracy at +23°C Thermistor | ±0.5°C / ±0.9°F |
| Channels | Single internal sensor only |
| Memory | 3000 samples |
| Communications | Via infra-red interface |
| Logging Start/Stop/LCD | Single multi-function button operation |
| Logging Frequency | Programmable between 1 second and 99 hours |
| Internal Sensor Response Time | T90 = 15 to 30 minutes in ambient air |
| Ambient Storage | As measurement range |
| Environmental Protection | IP65 BS EN 60529 IEC529 |
| Battery Type | Non-replacable 1/2 AA Lithium |
| Battery Life, based on 15 min log rate at +20°C / +68°F with alarms off | 24 months |
| Case Material | Food Safe polycarbonate |
| Dimensions | 88mm L x 80mm W x 35mm D |
| Weight | 77g/2.73 oz |



Technical Specification

WARRANTY


All Comark instruments have a minimum one year warranty unless otherwise stated. The warranty period for temperature probes is for six months and all other probes and electrodes are unwarranted because the conditions of use are beyond our control. The Comark warranty covers manufacturing defects and component failures on all products returned to Comark premises and applies worldwide. The warranty does not affect your statutory rights. In line with our policy of continuous development we reserve the right to alter any product specifications without notice. All products are covered by our Quality Management System which is compliant with BS EN ISO 9001:2008 for the design, manufacture, supply, service, repair and recalibration of electronic measuring instruments and equipment.

EVt Display


LCD display shows all essential information before, during and after logging. Automatic scroll function, available after logging has ended, enables the following data to be seen. Ideal for decision making before downloading or where this is not possible:




A. Maximum logged temperature




B. Minimum logged temperature



C. Average logged temperature



D. Cumulative time logged temperature are in programmed high alarm zone



E. Cumulative time logged temperature are in programmed low alarm zone

EV Software

There are two variants of the proven software package for programming, data retrieval and data storage.

EV Software - General Use Version

- Quick program function
- Extensive data presentation options in tabular and graphical form
- Selectable high and low alarm levels
- Selectable logging interval

EV Pro - Professional Version

Specification as general use version plus:

- Enhanced security options to aid compliance with 21CFR Part 11 requirements
- Additional data analysis including mean kinetic temperature and pasteurisation values.

BIOCOTE®

Selected Comark thermometers, probes and data loggers have BioCote's silver technology incorporated into instrument cases and probe handles at the time of manufacture. The antimicrobial finish inhibits the growth of bacteria, reducing the risk of cross-contamination and infection in the environment. BioCote® has been officially recognised for its benefits within the food industry with HACCP International Certification. HACCP International Certification supports organisations that demonstrate food safety excellence in non-food products that are designed for, or are commonly used in, the food industry. BioCote® is the only antimicrobial solution to be awarded HACCP International Certification.

Distributed by:

C206/2/EN © Comark Instruments

Comark Instruments
52 Hurricane Way
Norwich, Norfolk NR6 6JB, United Kingdom
Tel: 0844 815 6599
Fax: 0844 815 6598
Email: sales@comarkinstruments.com



Comark Instruments (USA)
PO Box 500
Beaverton, OR 97077, USA
Tel: (800) 555 6658
Fax: (503) 644 5859
Email: sales@comarkusa.com



Click on www.comarkinstruments.com or www.comarkusa.com for more information